

MANHOLES, TYPE A, 4'-DIAMETER,
TYPE 1 FRAME, CLOSED LID, SPECIAL
DETAIL

- 2. IF THE EXISTING SEWER PIPE IS CRACKED, BROKEN, OR OTHERWISE DAMAGED DURING THE REMOVAL, THE CONTRACTOR SHALL REPLACE THE DAMAGED SECTION OF PIPE WITH PIPE EQUAL AND SIMILAR IN ALL RESPECTS TO THE PIPE IN THE EXISTING SEWER, IN A CAREFUL WORKMANLIKE MANNER WITHOUT ADDITIONAL COMPENSATION.
- 3. TRENCH BACKFILL AND REPLACEMENT OF UNSUITABLE MATERIAL BELOW PLAN BEDDING GRADE WILL BE PAID FOR SEPERATELY.
- 4. ANY MATERIAL OR DEBRIS DEPOSITED IN THE FLOW LINE OF THE STORM SEWER DUE TO THE CONSTRUCTION OPERATIONS SHALL BE REMOVED UPON COMPLETION OF THE WORK.

¥		USER NAME = 2bookd	DESIGNED	***	DJB	REVISED -	
TLE NA	≈ ENTRAN		DRAWN	-	ENTRAN	REVISED -	
		PLOT SCALE = 1.00 '/ IN.	CHECKED	-	DAK	REVISED -	DEPA
-		PLOT DATE = 10/11/2011	DATE	~	09/07/11	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PUMP	STATION	24 ST	ORM SE	WER	IMPROVEMENTS					
DRAINAGE DETAILS										
SCALE: 1.00 '/ IN.	SHEET NO.	OF	SHEETS	STA.	TO STA.					